

Pressure

Digital atmospheric pressure sensor FDAD 12 SA, for barometric pressure Integrated in ALMEMO® D6 plug



General features and accessories, ALMEMO® D6 sensors
see page 15

Special features

- Digital atmospheric pressure sensor with temperature compensation
- Very accurate over a wide temperature range
- The value measured for atmospheric pressure can also be used to compensate other sensors on the ALMEMO® device (programming comment *P).
- Compact design, without pressure connection sleeve
- Can be connected directly to the measuring instrument.
- One measuring channel is programmed (at our factory).
- Atmospheric pressure (mbar, AP, p)

Technical Data

Digital atm. pressure sensor (integrated in ALMEMO® D6 plug)		ALMEMO® D6 plug	
Measuring range	300 to 1100 mbar	Refresh rate	1 second for all channels
Accuracy	±2.5 mbar in the range 700 to 1100 mbar at 23 °C ±5 K	Supply voltage	6 to 13 VDC
Operating range	-10 to +60 °C 10 to 90 % RH non-condensing	Current consumption	4 mA
Dimensions	62 x 20 x 7.6 mm		

Variants (including manufacturer's test certificate)

Digital atmospheric pressure sensor for barometric pressure, integrated in ALMEMO® D6 plug

Order no.
FDAD12SA

DAkkS or factory calibration KD92xx atmospheric pressure for digital sensor, see chapter „Calibration certificates“.
DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Pressure measuring connector for barometric pressure FDA 612 SA



- Compact design - can be plugged directly onto measuring instrument.
- Piezo-resistive pressure sensor - ensures high measuring accuracy.

Technical Data:

Measuring range	700 to 1050 mbar (total range 0 to 1050 mbar)	Sensor material	aluminum, nylon, silicone, silica gel, brass
Overload capacity	Maximum 1.5 times final value	Operating range	-10 to +60 °C, 10 to 90% RH, non-condensing
Accuracy	±0.5 % of final value	Dimensions	90 x 20 x 7,6 mm
Nominal temperature	25 °C		
Temperature drift	<±1 % final value at 0 to +60 °C		
Hose terminals	Ø 5 mm, 12 mm long		

Accessories

	Order no.		Order no.
Connecting cable, 0.2 meters	ZA9060AK1	Extension cable, 4 meters	ZA9060VK4
Extension cable, 2 meters	ZA9060VK2		

Variants (including manufacturer's test certificate)

Pressure measuring connector for barometric pressure with pressure terminal sleeve

Order no.
FDA612SA

DAkkS or factory calibration KD9xxx pressure for sensor or measuring chain (sensor + device), see chapter „Calibration certificates“.
DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.