

Sound Level

Sound Level Meter MA 86193 with ALMEMO® cable for measured value recording

10/2015 • We reserve the right to make technical changes.



- Digital Sound level meter
- Measuring according to IEC651, ANSI S1.4
- Measuring level range: 35 bis 130 dB
- Frequency weighting A or C
- Output maximum measured level
- Analogue output for connection to all ALMEMO® measurement devices for recording

Technical Data

Standard applied:	IEC651, ANSI S1.4	Output:	
Microphone:	Condenser microphone 12 mm	AC:	0.65 Vrms at FS (full scale) (output impedance approx. 600 Ω)
Frequency range:	31.5 Hz ... 8 KHz	DC:	10 mV/ dB (output impedance approx. 100 Ω)
Measuring range:	low: 35 ... 100 dB high: 65 ... 130 dB	Connection:	3.5mm Jack and plug with 2 m ALMEMO® cable
Dynamic range:	65 dB	Power supply:	one 9V battery
Frequency weighting:	A or C	Power life:	approx. 50 hrs (alkaline cell)
Time weighting:	fast (125ms) slow (1 s)	Operating temperature:	0 to 40°C
Accuracy:	± 2.0 dB (under reference conditions, 1000 Hz 94 dB)	Operating humidity:	10 to 90% r.H., non-condensing
Digital display:	LCD, 4 digits, resolution 0.1 dB	Sea level:	up to 2000 m
Display period:	0.5 sec.	Storage:	-10 to 60°C, 10 to 75 % r.H., non-condensing
Display functions:	Max Hold function alarm function „OVER“ (when input is out of range)	Dimensions:	240 (L) x 68 (W) x 25 (H) mm
Calibration:	electrical calibration with internal oscillator > (1000 Hz sine wave, 94 dB)	Mounting:	Threaded for tripod mounting (not included)
		Weight:	210 g (including battery)

Types

Sound Level Meter inclusive 9V battery and 2 m ALMEMO®-cable, windscreen, screwdriver, carrying case, instruction manual

Order no.

MA86193